

LEXICON™

Q U A R T Z C O M P O S I T E S I N K S

SUPPORTING PRODUCTS

LEXICON QUARTZ COMPOSITE SINKS CARE & MAINTENANCE TIPS

Lexicon Quartz Composite sinks have attitude and provoking characteristics, with rock-hard construction - sporting an 80% composition of quartz, the hardest, most durable constituent to granite. Lexicon sinks offer unsurpassed surface hardness along with scratch, chip, and heat resistance up to 535°F. The hygienic, non-porous surface is easy-to-clean, both stain and acid-resistant, does not absorb odors, and is even resistant against bacteria.

Cleaning Guide

Rinse the sink after each use with warm water and periodically use a nonabrasive scrubber pad or nonabrasive cleaner, such as liquid Soft Scrub sans bleach or Bar Keepers Friend. Even household baking soda can accomplish the same cleansing effect without the chemical additives. Always rinse well so gritty residue is not left in the sink.

Use of strong chemicals, abrasive powders, and steel wool pads will degrade the sink surface and make it more susceptible to staining.

Care Tips

- **NEVER** use any abrasive cleaning agents or scrub pads such as steel wool
- **NEVER** use straight bleach to clean or remove strains
- **NEVER** use commercial alkalis such as ammonia and/or caustic solutions



Use Bar Keepers Friend or Soft-Scrub (without bleach) for simple cleaning maintenance.



Household baking soda can accomplish the same cleansing effect as the above mentioned products.

Stain Problem	Cleaning Agent	Cleaning Method	When to Clean
Water spots and normal impurities	Water and a soft non-abrasive sponge.	Clean the sink with water and sponge. Use a dry cloth to dry it afterwards.	After every use.
Scratches caused by metal, pots, and pans	Mr.Clean® Magic Eraser® sponge.	Clean the sink with the eraser sponge. Rinse the sink with water and dry.	When necessary.
Rust, lime stains, and calcium buildup	Vinegar and commercial lime and rust remover.	Follow cleaning instructions when using a commercial lime and rust remover. Let the vinegar sit on the patch for at least 20 minutes. Rinse the sink with water and dry.	Monthly or when necessary. Interval depends on grade of water hardness.
Stubborn and aged stains	Household bleach and water solution.	Dilute 1 part bleach with 15 parts water. Let bleach sit on the stain overnight. Rinse the sink with water and dry.	When necessary.

The manufacturer and distributor will not be responsible or liable for any errors when using the following care and maintenance guide. Please consult a professional sink installer or fabricator for more details on proper care and maintenance of Lexicon Quartz Composite sinks.